

# SDK Objects

The SDK consists of the following classes.

## Personalization Class

Personalization is the main class. You can use an instance of this to invoke the different methods of SDK.

```
import personalization from '@personalization-js-sdk/web';
```

Create an instance of this class using the following code:

```
const personalizationInstance = personalization (  
  account,  
  user  
)
```

`account` and `user` are classes, and must be initialized to use as arguments for creating an instance of `personalization`. Refer to the objects below for information on how to initialize them.

## Account Object

This object contains information about the account.

Export this class using the following code:

```
export const account = {  
  domain: "", // Domain name  
  name: "", // Account name  
  instance: "", // Instance for the domain  
  shortname: "", // Short name for the account  
};
```

You must provide data for these variables.

Example code:

```
const account = {  
  domain: "monetate.mybigcommerce.com",  
  name: "a-3e41bf76",  
  instance: "p",  
  shortname: "monetatebc",  
};
```

## User Object

This object contains information about the user.

Create an instance of this class using the following code:

```
export const user = {  
  deviceId: "", // Device ID  
  monetateId: "", // Monetate ID  
  customerId: "", // Customer ID  
};
```

When creating this object, you must provide either the device ID or the Monetate ID. The recommended ID to use is the device ID.

You can define the Monetate ID as "auto" to make the SDK automatically generate the ID. If you do this, you must store the generated Monetate ID on your end.

The customer ID is optional. If this ID is defined, you must also pass it in all calls along with one of the other IDs. If you need to later change the customer ID, use the `setCustomerId` method.